The CLASSIC COLLECTION





FADED OAK CC44148C



CHOCOLATE OAK CC44113C

4.5 mm (7" x 48")

WEAR LAYER

12mil

INSTALLATION

Click

PRODUCT WARRANTIES

Lifetime Residential Warranty 1-Year Light Commercial Warranty Lifetime Structure Warranty Lifetime Waterproof Warranty

PACKAGING

20' Packaging: 28.80 sf/ct, 12 pc/ct, 38.32 lbs/ct, 55 ct/pl, 1,584 sf/pl, 19 pl/container, 30,096 sf/container

40' PACKAGING: 28.80sf/ct, 12 pc/ct, 38.32 Lbs/ct, 55 ct/pl, 1,584 sf/

pl, 25 pl/container, 39,600 sf/container



CLASSIC OAK CC44193C



DOVER OAK CC44104C



FADED PINE CC44133C



GREY OAK CC44122C



SEAGROVE CC44129C



EURO OAK CC44106C

Reaction to Fire EN13501-1: Pass Bfl-S1 Resistance to Heat ASTM F1514-03: Pass ^F<8 Static Load ASTM F970-07: Pass < 5 mils Coefficient of Friction: Pass > 0.5 Standard Neolite and leather, wet and dry Color Fastness to artificial light ISO 105-B02:

Color Fastness to rubbing ISO 105-E01: Pass >3 wet, >4 dry FloorScore Certified

Slip ResistantLimited Fifteen (15) Year Commercial Wear Warranty Lifetime Residential Wear Warranty

SOUND RATING

IIC- 55 STC-56

